



AGIP SUPERTRACTOR UNIVERSAL

AGIP SUPERTRACTOR UNIVERSAL is a multifunctional oil suitable for the lubrication of all parts (engines included) of practically all farm machinery of all makes and ratings, except for particularly heavily-loaded drives for which the makers specify an EP oil of API GL-5 level.

CHARACTERISTICS (TYPICAL FIGURES)

AGIP SUPERTRACTOR UNIVERSAL

SAE Grade		15W-30	15W-40
Viscosity at 100° C	mm ² /s	11,5	13,6
Viscosity at 40° C	mm ² /s	87	100
Viscosity at -20° C	mPa.s	5800	6100
Viscosity Index	-	130	135
Flash Point COC	°C	200	220
Pour Point	°C	-30	-27
Mass Density at 15° C	kg/l	0,880	0,884

PROPERTIES AND PERFORMANCE

- **AGIP SUPERTRACTOR UNIVERSAL** is formulated for the lubrication of all types of farm engines (gasoline and diesel, naturally-aspirated and turbocharged), as well as for all units found in modern agricultural machinery (transmission/clutch units, wet brakes, hydraulic and mechanical final-drives and power take-offs, hydraulic circuits. etc.).
- Careful choice of base stocks and additives imparts a high level of detergency-dispersancy, excellent oxidation stability and high Viscosity Index which guarantees elevated fluidity at low temperatures, as well as good anticorrosion, antistick and antisquawk properties for reduction of braking noise.
- **AGIP SUPERTRACTOR UNIVERSAL** ensures notable cost savings, as it greatly simplifies purchasing, storage and topping-up operations, eliminating the possibility of wrong applications and erroneous mixes.

SPECIFICATIONS

AGIP SUPERTRACTOR UNIVERSAL meets the requirements of the following services and specifications:

- ACEA E2
- ALLISON C4
- API CE-SF
- API CF-4
- API GL-4
- CAT TO-2
- CCMC D4
- FORD M2C 159B
- JOHN DEERE JDM J27
- M.B. 228.1
- MF M 1139
- ZF TE-ML 06B, 07B