eni i-Sint 5W-30



eni i-Sint 5W-30 is a High-Tech top synthetic engine oil in mid SAPS quality for modern passenger car gasoline and diesel engines with and without DPF also at prolonged oil-change intervals.

Characteristics (typical figures)

SAE Grade		5W-30
Viscosity at 100 °C	mm²/s	12
Viscosity at 40 °C	mm²/s	74
Viscosity at -30 °C	mPa∙s	6100
Viscosity Index	-	161
Flash Point	°C	210
Pour Point	°C	-42
Mass Density at 15 °C	kg/l	0.852

Properties and Performance

eni i-Sint 5W-30 excels through:

- excellent wear protection
- optimum cold start properties
- proven fuel saving
- low oil consumption
- gentle treatment of the catalysts through low phosphorus content
- meets the requirements concerning DPF (mid SAPS) posed by some relevant manufacturers

Specifications

eni i-Sint 5W-30 is officially approved or meets the requirements of the following service specifications:

- * ACEA A3/B4-04
- * ACEA C3
- * VW 504 00 + 507 00
- * MB-Approval 229.51
- * BMW LongLife 04
- * PORSCHE C30

Via Laurentina 449, 00142 Rome Exchange Phone +39 06 5988.1 www.eni.com