



# eni i-Sint professional 5W-40

eni i-Sint professional 5W-40 is a synthetic engine lubricant of high performances designed to lubricate cars of the latest model powered with either gasoline or Diesel engines and operating even under the severest conditions.

## Characteristics (typical figures)

SAE Grade		5W-40
Viscosity at 100° C	mm <sup>2</sup> /s	13.8
Viscosity at 40° C	mm <sup>2</sup> /s	84
Viscosity at -30° C	mPa·s	6300
Viscosity Index	-	170
Flash Point COC	°C	240
Pour Point	°C	-33
Mass Density at 15° C	kg/l	0.856

## Properties and performance

- The viscosity of **eni i-Sint professional 5W-40** remains virtually unaltered after mileage accumulation, thus maintaining the original properties of the product.
- The synthetic formulation with high thermal stability reduces oil consumption due to low volatility.
- **eni i-Sint professional 5W-40** has outstanding detergent-dispersant properties and minimizes the formation of lacquer and varnish, as well as sludge and other engine deposits. Hence the oil helps prevent ring sticking and keeps pistons clean, while maintaining potential deposits in suspension.
- **eni i-Sint professional 5W-40** is free-flowing at cold temperatures which allows easier engine start-up.

## Specifications and approvals

eni i-Sint professional 5W-40 meets the requirements of the following services and specifications:

- API SL/CF
- ACEA A3/B4-04